

FULL-E+ 1.5 PRO



SPECS

TELAIO	
TAGLIE	S, M, L, XL
COLORAZIONI	Black/Blue, Black/Red
TELAIO	ALUXX-SL Grade Aluminum
FORCELLA	Fox Rhythm 34 27,5+ 140mm, Grip Damper, tapered steerer 'Boost' 110x15QR
AMMORTIZZATORE	RockShox Deluxe RT, DebonAir high volume shock, 185x52.5mm Trunnion mount, custom tuned
COMPONENTISTICA	
MANUBRIO	Giant Connect TR 780x31,8mm
ATTACCO MANUBRIO	Giant Connect [50 S, 60 M/L, 70XL]
TUBOSELLA	Giant Contact Switch, remote height adjust [100 S/M, 125 L, 150 XL]
SELLA	Giant Contact neutral
PEDALI	Giant Original MTB-Sport, Aluminium Platform, CrMo, replaceable pins
SISTEMA DI TRASMISSIONE	
LEVE DEL CAMBIO	Shimano Deore 2x10sp
DERAGLIATORE	Shimano Deore
CAMBIO	Shimano XT shadow+, 10sp
FRENI	Shimano BR-MT500 203mm Disc
COMANDI FRENO	Shimano BL-MT500 i-spec II
PACCO PIGNONI	Shimano HG50-10 11-36T, 10sp
CATENA	KMC X.10e, e-bike optimized
GUARNITURA	Custom forged crankset by FSA, 28/38T, Boost 2x spider
RUOTE	
CERCHI	Giant GE35, Tubeless ready, 27.5" 35mm aluminum, e-bike optimized
MOZZI	Giant eTracker Boost, Sealed Cartridge bearing, IS 6-bolt, [F] 110x15 [R] 148x12mm Thru-axle, e-bike optimized
RAGGI	Giant eTracker Boost, Sealed Cartridge bearing, IS 6-bolt, [F] 110x15 [R] 148x12mm Thru-axle, e-bike optimized
COPERTURE	Maxxis Rekon 27.5x2.6" foldable, Double Compound, Exo protect, Tubeless
EXTRAS	Giant EnergyPak 4A fast charger
TECNOLOGIA IBRIDA	
MOTORE	Giant SyncDrive Pro
SENSORS	Giant PedalPlus 4-sensor technology
DISPLAY	Giant RideControl EVO, grip launch control with walk assist, mini USB charger
BATTERIA	Giant EnergyPak 500, 36V 13.8Ah Rechargeable Lithium-Ion

CARATTERISTICHE

- Giant SyncDrive Pro central motor, performance tuned
- Giant EnergyPak500 lithium-ion battery for longest range
- Fox Rhythm 140mm travel
- Shimano Deore/XT 2x10-speed Drivetrain
- Shimano hydraulic brakes
- Remote height adjust seatpost
- Color: Black / Blue



Prezzo: € 4.199

GEOMETRIA

TELAIO	S	M	L	XL
Lunghezza tubo sella (mm)	431	450	500	530
Angolo tubo sella	73,0°	73,0°	73,0°	73,0°
Lunghezza tubo orizzontale (mm)	565	590	610	635
Lunghezza tubo sterzo (mm)	125	125	140	160
Angolo sterzo	67,0°	67,0°	67,0°	67,0°
Rake forcella (mm)	42	42	42	42
Trail (mm)	109	109	109	109
Interasse (mm)	1143	1168	1190	1217
Lunghezza carro posteriore (mm)	463	463	463	463
Drop movimento centrale (mm)	12	12	12	12
Stack (mm)	610	610	624	642
Reach (mm)	378	403	419	438
Altezza stand over (mm)	768	769	806	832
Larghezza manubrio c/c (mm)	780	780	780	780
Lunghezza attacco manubrio (mm)	50	60	60	70
Larghezza pedivella (mm)	170,0	170,0	170,0	170,0
Dimensione ruote	27.5+	27.5+	27.5+	27.5+

Le specifiche tecniche sono soggette a variazioni senza obbligo di preavviso.