



SPECS

TELAIO	
TAGLIE	XS, S, M
COLORAZIONI	Black/Pink/Orange
TELAIO	ALUXXSL aluminum, for integrated EnergyPak system, Overdrive 1½ - 1½" head tube, internal cable routing, integrated carrier, kickstand & fender mounts
FORCELLA	SR Suntour XCR 32 LO-R 120mm travel, 15QR, Tapered 1½ - 1½" steerer, lockout
COMPONENTISTICA	
MANUBRIO	Giant Connect Trail 730x31,8mm
ATTACCO MANUBRIO	Giant Connect
TUBOSELLA	Giant Connect
SELLA	Liv Contact Upright
PEDALI	Aluminum Platform
SISTEMA DI TRASMISSIONE	
LEVE DEL CAMBIO	Shimano Acera M3000 2x9sp
DERAGLIATORE	Shimano Deore
CAMBIO	Shimano Deore Shadow, 9sp
FRENI	Shimano M315 180/200mm Disc
COMANDI FRENO	Shimano M315
PACCO PIGNONI	Shimano HG 201-9 11-36T silver
CATENA	KMC X9e, e-bike optimized
GUARNITURA	Custom forged crankset by FSA, 24/38T
RUOTE	
CERCHI	Giant GE35, Tubeless ready, 27.5" 35mm aluminum, e-bike optimized
MOZZI	Giant eTracker Boost, Sealed Cartridge bearing, IS 6-bolt, [F] 110x15 [R] 148x12mm Thru-axle, e-bike optimized
RAGGI	Giant eTracker Boost, Sealed Cartridge bearing, IS 6-bolt, [F] 110x15 [R] 148x12mm Thru-axle, e-bike optimized
COPERTURE	Maxxis Forekaster 27.5x2.6, foldable, 60 TPI, EXO
EXTRAS	Giant EnergyPak 4A fast charger
TECNOLOGIA IBRIDA	
MOTORE	Giant SyncDrive Sport
SENSORS	Giant PedalPlus 4-sensor technology
DISPLAY	Giant RideControl Charge, grip launch control with walk assist, mini USB charger
BATTERIA	Giant EnergyPak 500, 36V 11.3Ah Rechargeable Lithium-Ion

CARATTERISTICHE

- Giant SyncDrive Sport, 80Nm central motor, powered by YAMAHA
- Giant EnergyPak500 lithium-ion battery
- SR Suntour XCR 32 LO-R 120mm-travel fork with lockout
- Shimano Deore 2x9-speed drivetrain
- Shimano M315 hydraulic disc brakes
- Color: Black/Pink/Orange

Prezzo: € 2.499

GEOMETRIA

TELAIO	XS	S	M	L
Angolo tubo sella	74,0°	73,5°	73,0°	73,0°
Lunghezza tubo orizzontale (mm)	550	565	585	600
Lunghezza tubo sterzo (mm)	110	115	135	150
Angolo sterzo	68,0°	68,0°	68,0°	68,0°
Interasse (mm)	1116	1126	1142	1158
Lunghezza carro posteriore (mm)	475	475	475	475
Stack (mm)	612	617	635	649
Reach (mm)	374	382	390	401
Altezza stand over (mm)	674	696	742	763
Larghezza pedivella (mm)	170,0	170,0	170,0	170,0

Le specifiche tecniche sono soggette a variazioni senza obbligo di preavviso.