



SPECS

TELAIO	
TAGLIE	S, M, L, XL
COLORAZIONI	Black/Teal/Yellow
TELAIO	ALUXX-SL Grade Aluminum
FORCELLA	RockShox Yari RC 27.5+, Solo Air 160mm travel, Boost 15X110 Maxle Ultimate, Crown adjust compression damper
AMMORTIZZATORE	RockShox Deluxe RT, DebonAir high volume shock, 185x52.5mm Trunnion mount, custom tuned
COMPONENTISTICA	
MANUBRIO	Giant Contact SL DH 800x31,8mm
ATTACCO MANUBRIO	Giant Connect [50 S/M/L, 60 XL]
TUBOSELLA	Giant Contact Switch, remote height adjust [100 S/M, 125 L, 150 XL]
SELLA	Giant Contact neutral
PEDALI	Giant Original MTB-Sport, Aluminium Platform, CrMo, replaceable pins
SISTEMA DI TRASMISSIONE	
LEVE DEL CAMBIO	Shimano SLX 1x11-sp
DERAGLIATORE	MRP 1X-D-Mount TR chain guide
CAMBIO	Shimano XT Shadow+, 11sp
FRENI	Shimano BR-M6000 200/200mm Disc
COMANDI FRENO	Shimano BL-M6000 i-spec II
PACCO PIGNONI	Shimano HG-M7000, 11-46T, 11s
CATENA	KMC X.11e EcoProteQ, e-bike optimized
GUARNITURA	Praxis Works 36T Cold Forged 4130 premium plate steel Wavetm chainring, custom crankset, "Boost" 4-bolt 104BCD Yamaha specific spider
RUOTE	
CERCHI	Giant GE35, Tubeless ready, 27.5" 35mm aluminum, e-bike optimized
MOZZI	Giant eTracker Boost, Sealed Cartridge bearing, IS 6-bolt, [F] 110x15 [R] 148x12mm Thru-axle, e-bike optimized
RAGGI	Giant eTracker Boost, Sealed Cartridge bearing, IS 6-bolt [F] 110x15mm, 28h, [R] 148x12mm Thru-axle, e-bike optimized, 32h
COPERTURE	Maxxis Rekon 27.5x2.6" foldable, EXO protect, Dual Compound [R], 3C Maxx Grip [F], Tubeless
EXTRAS	Giant EnergyPak 4A fast charger
TECNOLOGIA IBRIDA	
MOTORE	Giant SyncDrive Pro
SENSORS	Giant PedalPlus 4-sensor technology
DISPLAY	Giant RideControl EVO, grip launch control with walk assist, mini USB charger
BATTERIA	Giant EnergyPak 500, 36V 13.8Ah Rechargeable Lithium-Ion

CARATTERISTICHE

- Giant SyncDrive Pro central motor, performance tuned
- Giant EnergyPak500 lithium-ion battery for longest range
- Shimano SLX/XT 1x11-speed drivetrain
- RockShox Yari RC 160mm fork
- Contact Switch remote height adjust seatpost
- Color: Black/Teal/Yellow



Prezzo: € 4.599

GEOMETRIA

TELAIO	S	M	L	XL
Lunghezza tubo sella (mm)	431	450	500	530
Angolo tubo sella	72,5°	72,5°	72,5°	72,5°
Lunghezza tubo orizzontale (mm)	565	590	610	635
Lunghezza tubo sterzo (mm)	125	125	140	160
Angolo sterzo	66,5°	66,5°	66,5°	66,5°
Rake forcella (mm)	51	51	51	51
Trail (mm)	103	103	103	103
Interasse (mm)	1156	1181	1203	1230
Lunghezza carro posteriore (mm)	463	463	463	463
Drop movimento centrale (mm)	5,0	5,0	5,0	5,0
Stack (mm)	621	621	635	653
Reach (mm)	367	392	408	427
Altezza stand over (mm)	776	777	814	840
Larghezza manubrio c/c (mm)	800	800	800	800
Lunghezza attacco manubrio (mm)	50	50	50	60
Larghezza pedivella (mm)	170,0	170,0	170,0	170,0
Dimensione ruote	27.5+	27.5+	27.5+	27.5+

Le specifiche tecniche sono soggette a variazioni senza obbligo di preavviso.