EMBOLDEN E+ 1

SPECS

TELAIO	
TAGLIE	XS, S, M, L
COLORAZIONI	Black
TELAIO	ALUXX SL-grade aluminum, 120mm FlexPoint suspension system
FORCELLA	RockShox Recon RL, 130mm travel, Lockout, 110x15mm MaxleLite
AMMORTIZZATORE	RockShox Monarch RT, High Volume, 184x44mm, custom tuned
COMPONENTISTICA	
MANUBRIO	Giant Connect TR Riser
ATTACCO MANUBRIO	Giant Contact
TUBOSELLA	Giant Contact Switch, dropper, 30,9mm, (XS:75, S:100, M:125, L:150)
SELLA	Liv Contact upright
PEDALI	-
SISTEMA DI TRASMISSIONE	
LEVE DEL CAMBIO	SRAM SX Eagle 12-speed
DERAGLIATORE	-
CAMBIO	SRAM SX Eagle 12-speed
FRENI	Shimano MT420, 4-piston brakes, 203mm
COMANDI FRENO	Shimano MT401 Hydraulic Disc
PACCO PIGNONI	SRAM PG-1210, 11-50T, 12-Speed
CATENA	SRAM SX Eagle PowerLock, 12-speed
GUARNITURA	SRAM X-Sync Eagle 38T 104BCD chainring Forged Alloy minimal Q-factor, 36T Steel Direct Mount ring (XS/S:160, M/L:165)
RUOTE	
DROP MOVIMENTO CENTRALE	N/A
CERCHI	Giant AM 27.5+, Tubeless ready, 35mm inner width, e-bike optimized
MOZZI	Giant eTracker Boost, Sealed Cartridge bearing, IS 6-bolt, [F] 110x15 [R] 141x9mm Quick-Release, e-bike optimized
RAGGI	Stainless Steel
COPERTURE	Maxxis Rekon 27.5x2.6", Exo protect, Tubeless Ready
EXTRAS	Giant EnergyPak 6A Smart charger
TECNOLOGIA IBRIDA	
MOTORE	Giant SyncDrive Sport, 70Nm, 350% tuneable support with automatic smart support
SENSORS	Giant PedalPlus 6-sensor technology
DISPLAY	Giant RideControl ONE, remote button
BATTERIA	Giant EnergyPak Smart 500, 36V 13.8Ah integrated Lithium-Ion

CARATTERISTICHE

- Telaio: ALUXX SL-grade aluminum, 120mm FlexPoint suspension system
- Forcella: RockShox Recon RL, 130mm travel, Lockout, 110x15mm MaxleLite
- Leve del cambio: SRAM SX Eagle 12-speed
- Guarnitura: SRAM X-Sync Eagle 38T 104BCD chainring Forged Alloy minimal Q-factor, 36T Steel Direct Mount ring (XS/S:160, M/L:165)
- Colorazioni: Black

Prezzo: € 3.599,00

GEOMETRIA

TELAIO	XS	S	M	L
Lunghezza tubo sella (mm)	380	406	445	490
Angolo tubo sella	74,0°	74,0°	74,0°	74,0°
Lunghezza tubo orizzontale (mm)	565	580	595	610
Lunghezza tubo sterzo (mm)	100	100	110	120
Angolo sterzo	67,5°	67,5°	67,5°	67,5°
Rake forcella (mm)	46	46	46	46
Trail (mm)	103,3	103,3	103,3	103,3
Interasse (mm)	1147	1162	1178	1194
Lunghezza carro posteriore (mm)	465	465	465	465
Drop movimento centrale (mm)	20	20	20	20
Stack (mm)	592	592	602	611
Reach (mm)	395	410	422	435
Altezza stand over (mm)	710	728	756	789
Larghezza manubrio c/c (mm)	750	750	780	780
Lunghezza attacco manubrio (mm)	40	40	50	50
Larghezza pedivella (mm)	165	165	170	170
Dimensione ruote	27.5+	27.5+	27.5+	27.5+

Le specifiche tecniche e i colori sono soggette a variazioni senza obbligo di preavviso. Taglie disponibili per l'Italia da verificare con il B2B per ogni modello.